


TURBO 130




PLC Control
Touch Screen Panel



Platform in/out
Movement



Automatic Pad Clean Function



Maximum Space for product/image
with advantage of auto pad clean function

FEATURES

- **Solely single color pad printer**
- **Platform in/out movement**
- Aluminium cast machine frame
- Pneumatic power machine operation
- Sealed ink cup system
- Able to print $\varnothing 140\text{mm}$
- Combatible for steel, thin steel pad polymer plates
- PLC touch screen panel
- Interface in place
- Automatic pad clean
- Pad stroke and speed adjustment
- Special functions:
double ink/cycle print, dwell and delay
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement

SPECIFICATIONS

Ink cup size	up to $\varnothing 125, 130\text{ mm}$
Printing plate size	100x250, 150x300mm
Max Speed	900 Cyc/hr
Pad compression	1870N
Pad cylinder	$\varnothing 63\text{mm}$
Pad carriage stroke	247mm (linear guide rail)
Power	110/220 V
Air consumption	ca. 228 ltr/min
Accuracy +/-	0,05mm
Size (LxWxH)	974x810x1,680mm
Weight	380 kg



www.kent-stuttgart.de info@kent-stuttgart.de
Fon: 0711/40950-0 • Fax: 0711/40950-50
Kesselstraße 46 • 70327 Stuttgart-Wangen